



4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera

DH-H4A



Series Overview

The Hero Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. These highly sensitive cameras deliver crystal clear images and offer 360-degree monitoring without blind spots. Their powerful functions, such as human detection and auto tracking, not only assist with the accurate detection and continuous tracking of targets, but also reduce the occurrence of false alarms. It also features two-way talk, which allows you to freely communicate with your scene anytime, anywhere. Information is synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small scenes such as shops and restaurants.



4MP

Clear images with sharp details



One Camera for 360° View

360° monitoring without blind spots



Human Detection

Focuses on what matters and reduces false alarms



Day&Night

Clear images even at night



Auto Tracking

Automatic tracking of targets



Two-way Talk

Communication anytime, anywhere



One-click Privacy Mode

Protects your privacy



H.265

Advanced H.265 compression technology




DMSS App

Easy to use



Micro SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.





Specifications

Camera

| | |
|----------------------------|---------------------------------------|
| Image Sensor | 1/3" CMOS |
| Max. Resolution | 2560 (H) × 1440 (V) |
| Electronic Shutter Speed | Auto/Manual 1/3 s–1/100,000 s |
| Illumination Distance | Up to 10 m (32.81 ft) (IR) |
| Illuminator On/Off Control | Auto |
| Illuminator Number | 1 (IR LED) |
| Angle Adjustment | Pan: 0° to 355°; Tilt: -5° to +80° |
| Max. Aperture | 3.6 mm: F2.0 |
| Field of View | 3.6 mm: H: 74°; V: 41°; D: 88° |

Video & Audio

| | |
|-------------------|---|
| Video Compression | H.265 |
| Video Frame Rate | Main stream: 2560 × 1440 @25 fps Sub stream: 640 × 480 @25 fps |
| Resolution | 4M (2560 × 1440); VGA (640 × 480) |
| Video Bit Rate | H.265: 80 kbps–4096 kbps |
| Day/Night | Auto(ICR)/Color/B/W |
| WDR | DWDR |
| Motion Detection | OFF/ON |
| Image Rotation | 0°/180° |
| Built-in MIC | Yes, built-in Mic |
| Built-in Speaker | Yes, built-in speaker |
| Audio Compression | G.711a |


Network

| | |
|---------------------|---|
| Network Port | RJ-45 (10/100 Base-T) |
| Wi-Fi | IEEE 802.11b/g/n 2.4–2.4835 GHz, 2.4 G; EIRP≤20 dBm |
| Storage | Micro SD card (up to 256 GB) |
| Management Software | DMSS |
| Mobile Client | iOS;Android |

General

| | |
|-----------------------|---|
| Certifications | CE |
| Power Supply | 5 VDC, 1A |
| Power Consumption | Basic: 1.8 W; Max. (video stream acquiring + IR + PTZ Rotation): 3.6 W |
| Operating Temperature | -10 °C to +45 °C (+14 °F to +113 °F) |
| Operating Humidity | ≤ 95% |
| Casing Material | Plastic |
| Product Dimensions | φ77.8 mm × 108.1 mm (φ3.06" × 4.26") |
| Net Weight | 204.2 g (0.45 lb) |

What's in the box



× 1

Tools:

- Installation Position Map×1
- Mounting Platex1
- Screw Package×1

Documents:

- QR Codex1
- Quick Start Guidex1
- Legal and regulation information×1

Power:

- Power Adapter×1
- Power Cable×1

