

ASR1200E ASR1200E-D

Water-proof RFID Reader



- Connect to third party controller by wiegand protocol;
- RS485 support longer distance;



- Outdoor use;


Overview

The reader support wiegand, it means you can integrate it with the third party controllers. Certainly, any Dahua access controller can connect to the reader by using wiegand or RS485. For RS485, it support 100m distance when power supply from controller. If power supply separate, it can extend to 1000m. The slim and water-proof design can make it used in any environment.

Features


- Wiegand34(26 optional) bits RS-485 protocol
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- Water-proof design
- Red, blue and green indicator LEDs
- Surface mounted installation

Connection



RS485 wiring

AWG 24, twisted-pair cable;
RS485: 1000m;
Power: 100m;



Wiegand wiring

AWG 24, twisted-pair cable;
Wiegand: 40m;
Power: 100m;
LED cable control the reader
buzzer and LED light;

Technical Specification

Mode	ASR1200E	ASR1200E-D
System		
Main Processor	8 Bit	
Read		
Read Format	13.56MHz	125KHz
Read Range	3-6cm (max.)	
Reading time	<0.1s	
Function		
Water-proof	IP67	
Interface		
To Controller	RS485,Wiegand 34(26 optional)	
General		
Beep Tone	Buzzer	
Ingress protection	IP67, water resistant	
Power Supply	9-15VDC/100mA	
Working Environment	-30°C~60°C	
Working Humidity	≤95%	
Dimension(W×D×H)	96mm*43mm*17mm	
Weight	0.1Kg	

Dimensions

