


DS-2DE4220W Series 2.0 MP 4-inch 20X Network PTZ Dome Camera



Hikvision DS-2DE4220W Series PTZ Dome Cameras are able to capture high quality images in low light environment.

Embedded with 1/2.8" progressive scan CMOS sensor makes DWDR and 2MP real-time resolution possible. With the 20X optical zoom Day/Night lens, the camera offers more details over expansive areas.

Hikvision DS-2DE4220W Series PTZ Dome Cameras also features a wide range of functions, and can be widely applied in forest, freeway, railway, airport, harbor, park, street, bus station, etc..

Key Features

- 1/2.8" Progressive Scan CMOS
- 1920 × 1080@30fps Resolution
- 20X Zoom
- DWDR
- 3D Positioning
- PoE (802.3at, class 4)
- Hik Cloud P2P
- IP66



Function Description

Basic Function

- H.264/MJPEG video compression, up to 1920 × 1080@30fps resolution
- PoE (802.3at)
- Mirror, and one-key restore
- Supports Hikvision SDK, ONVIF, CGI, PSIA, and Hik Cloud P2P
- 3D positioning
- ±0.1° preset accuracy
- Power-off memory: restore PTZ and Lens status after reboot

Smart Function

- Smart detection: intrusion detection, line crossing detection, audio exception detection, motion detection, and video tampering detection
- Smart recording: edge storage, smart search in smart NVR, and VCA playback
- Smart image enhancement: Digital WDR (Wide Dynamic Range), HLC (High Light Compensation), Defog, EIS (Electronic Image Stabilization)
- Smart encoding: low bitrate, and ROI (Region of Interest) encoding
- Smart alarm: alarm for network disconnection, IP address conflict, HDD full, HDD error, and illegal login

Camera Function

- 20 × optical zoom, 16 × digital zoom
- Auto iris, auto focus, auto white balance, backlight compensation and 3D DNR
- Min. Illumination: 0.05Lux@(F1.6, AGC ON) (Color), 0.01Lux@(F2.0, AGC ON) (B/W)

PTZ Function

- 0° to 360° pan range, and 5° to 90° tilt range
- 0.1° to 160°/s manual pan speed, and 0.1° to 120°/s manual tilt speed
- 300 programmable presets
- 8 patrols, up to 32 presets for each patrol
- Proportional zoom, and park action
- 1 alarm input, 1 alarm output, and alarm linkage which is able to perform alarm actions, such as Send Email, Notify Surveillance Center, Upload to FTP/Memory Car/NAS, Trigger Recording, etc.

Network Function

- Micro SD/SDHC/SDXC card storage, up to 128GB
- Built-in microphone with 1 audio input and 1 audio output
- Supports NAS storage, and able to transmit the videos from memory card to the NAS after network resumed
- HTTPS encryption and IEEE 802.1x port-based network access control
- Supports three streams, H.264/MJPEG video compression, and baseline, main and high profiles
- Supports multiple network protocols: IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, PPPoE, Bonjour

Specification

| Camera Module | |
|-------------------------------|--|
| DS-2DE4220W | |
| Image Sensor | 1/2.8" progressive scan CMOS |
| Min. Illumination | Color: 0.05 Lux @ (F1.6, AGC ON), B/W: 0.01Lux @ (F1.6, AGC ON) |
| Day & Night | ICR Switch |
| Focus Mode | Auto/Semi-Auto/Manual |
| Shutter Speed | 1/1 to 1/10,000s |
| Digital Zoom | 16× |
| White Balance | Auto/manual/ATW (auto tracking white balance)/indoor/outdoor/daylight lamp/sodium lamp |
| AGC | Auto/Manual |
| Backlight Compensation | Support |
| Wide Dynamic Range | Support |
| DNR (Digital Noise Reduction) | Support |
| Privacy Mask | 8 programmable privacy masks |
| Lens | |
| Focal Length | 4.7 to 94mm, 20× |
| Field of View | 61.4° to 2.9° (wide-tele) |
| Working Distance | 10 to 1000mm (wide-tele) |
| Zoom Speed | Approx. 3s (optical lens, wide-tele) |
| Aperture Range | F1.6 to F3.5 |
| Smart | |
| Smart Detection | Intrusion detection, line crossing detection, audio exception detection, motion detection, and video tampering detection |
| Smart Recording | Edge storage, smart search in smart NVR, and VCA playback |
| Smart Image Enhancement | WDR, HLC, Defog, EIS |
| Smart Encoding | Low bitrate, and ROI (Region of Interest) encoding |
| Smart Alarm | Alarm for network disconnection, IP address conflict, HDD full, HDD error, and illegal login |
| Network | |
| Main Stream | 50Hz: 25fps (1920×1080,1280×960,1280×720), 50fps (1280×960,1280×720) 60Hz: 30fps(1920×1080,1280×960,1280×720), 60fps (1280×960,1280×720) |
| Sub-Stream | 50Hz: 25fps(704×576,640×480,352×288) 60Hz: 30fps(704×480,640×480,352×240) |
| Third Stream | 50Hz: 25fps (1920×1080,1280×960,1280×720,704×576,640×480,352×288) 60Hz: 30fps(1920×1080,1280×960,1280×720,704×480,640×480,352×240) |
| Video Compression | H.264/MJPEG |
| Audio compression | G.711alaw/G.711ulaw/G.722/G.726/MP2L2/PCM |
| Protocols | IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, PPPoE, Bonjour |
| Simultaneous Live View | Up to 20 users |
| User/Host | Up to 32 users, 3 levels: Administrator, Operator, and User |
| Security Measures | User authentication (ID and PW), host authentication (MAC address), IP address filtering, HTTPS encryption and IEEE 802.1x port-based network access control |
| Pan and Tilt | |
| Movement Range | Pan: 360°, Tilt: 5° to 90° |
| Movement Speed | Pan: 0.1° to 160°/s, Tilt: 0.1°to 120°/s |
| Preset No. | 300 |

| | |
|---------------------------|--|
| Patrol | 8 patrols, up to 32 presets per patrol |
| Park Action | Preset/patrol/pattern/auto scan/tilt scan/random scan/frame scan/panorama scan |
| Scheduled Task | Preset/patrol/pattern/auto scan/tilt scan/random scan/frame scan/panorama scan/dome reboot/dome adjust/aux output |
| Proportional Zoom | Support |
| Power-off Memory | Support |
| Position Display | On/ Off |
| System Integration | |
| Alarm I/O | 1 alarm input, 1 alarm output |
| Alarm Linkage | Alarm actions, such as Send Email, Notify Surveillance Center, Upload to FTP/Memory Car/NAS, Trigger Recording etc. |
| Audio I/O | 1 audio input, 1 audio output |
| Ethernet | 1 RJ45 10M/100M Ethernet interface |
| Memory Card | Built-in memory card slot, supporting SD/SDHC/SDXC, up to 128GB |
| Client | iVMS-4200 |
| Web Browser | IE7+, Chrome18+, Firefox5.0+, Safari5.02+ |
| General | |
| Power | AC 24V, and PoE (802.3at) Max.: 18W |
| Working Temperature | Indoor Models: -10°C to 50°C (-14°F to 122°F) Outdoor Models: -30°C to 65°C (-22°F to 149°F) |
| Working Humidity | ≤ 90% |
| Protection Level | IP 66 (outdoor models), TVS 4,000V lightning protection, and surge protection |
| Dimensions(mm) | In-Ceiling Mounting Indoor Models: Φ165×168mm (Φ6.5"×6.6") Ceiling Mounting Indoor Models: Φ165×179.5mm (Φ6.5"×7.1") Outdoor Models: Φ179.4×239.5mm (Φ7.1"×9.4") |
| Weight | Approx. 2.0kg (4.4lb) |


Available Model

DS-2DE4220W-AE: PoE (802.3at, class4) & AC24V, outdoor model

DS-2DE4220W-AE3: PoE (802.3at, class4) & AC24V, indoor model

* The indoor models support both the in-ceiling mounting and the ceiling mounting.

Dimension



Accessories



DS-1618Z

Short-Arm Wall Mounting



DS-1661ZJ

Pendent Mounting (20cm)



DS-1662ZJ

Pendent Mounting (50cm)



DS-1663ZJ

Ceiling Mounting

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com

0503061060614