

## DS-2CD1721FWD-I (Z) 2.0 MP CMOS Vari-Focal Network Dome Camera



### Key Features

- 1/2.8" progressive scan CMOS
- Up to 2.0 megapixel
- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens
- Up to 30 m IR range
- Dual stream
- 120 dB WDR (Wide Dynamic Range)
- 3D DNR (Digital Noise Reduction)
- PoE (Power over Ethernet)
- IP67, IK10
- Mobile monitoring via Hik-Connect or iVMS-4500




## Specification

| <b>Camera</b>                  |  |
|--------------------------------|--|
| Image Sensor                   | 1/2.8" progressive scan CMOS   |
| Min. Illumination              | Color: 0.01 Lux @(F1.2, AGC ON), 0 Lux with IR   |
| Shutter Speed                  | 1/3 s to 1/100, 000 s, support slow shutter  |
| Lens                           | 2.8 mm to 12 mm @F1.4, horizontal field of view: 100° to 35°   |
| Lens Mount                     | Φ14  |
| Day & Night                    | IR cut filter with auto switch   |
| 3-Axis Adjustment              | Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360°   |
| DNR (Digital Noise Reduction)  | 3D DNR   |
| WDR (Wide Dynamic Range)       | 120 dB   |
| <b>Compression Standard</b>    |  |
| Video Compression              | Main stream: H.264+/H.264<br>Sub stream: H.264/MJPEG   |
| H.264 Type                     | Baseline profile/Main profile  |
| Video Bit Rate                 | 32 Kbps to 8 Mbps  |
| <b>Image</b>                   |  |
| Max. Resolution                | 1920 × 1080  |
| Main Stream<br>Max. Frame Rate | 50Hz: 25fps @(1920 × 1080, 1280 × 960, 1280 × 720)<br>60Hz: 30fps @(1920 × 1080, 1280 × 960, 1280 × 720)               |
| Sub-stream<br>Max. Frame Rate  | 50Hz: 25fps @(704 × 576, 640 × 360, 352 × 288, 320 × 240)<br>60Hz: 30fps @(704 × 480, 640 × 360, 352 × 240, 320 × 240) |
| Image Settings                 | Brightness, saturation, contrast, sharpness are adjustable via web browser or client software                          |
| Day/Night Switch               | Support auto, scheduled  |
| Others                         | Mirror, BLC (area configurable), region of interest (support 1 fixed region)   |
| <b>Network</b>                 |  |
| Network Storage                | Support micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS, SMB/CIFS), ANR                                     |
| Detections                     | Motion detection   |
| Alarms                         | Video tampering, network disconnected, IP address conflicted, HDD full, HDD error                                      |
| Protocols                      | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour    |
| Standard                       | ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI   |
| General Function               | One-key reset, anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter        |
| <b>Interface</b>               |  |
| Communication Interface        | 1 RJ45 10M/100M self-adaptive Ethernet port  |
| Video Output (Without-Z)       | 1Vp-p composite output (75Ω/BNC)   |
| Reset                          | Support  |
| <b>General</b>                 |  |
| Operating Conditions           | -30 °C to 60°C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)  |
| Power Supply                   | DC12V ± 25%, PoE (802.3af)   |
| Power Consumption              | Max. 5.5 W/11 W (With -Z)  |
| Protection Level               | IP67, IK10   |
| IR Range                       | Up to 30 m   |
| Dimensions                     | Φ 141 mm × 99.9 mm (5.6" × 3.9")   |
| Weight                         | 800 g (1.76 lb.)   |

## Available Models

DS-2CD1721F-I (Z)

## Dimension



## Accessory



**DS-1227ZJ**  
In-ceiling Mounting Bracket



**DS-1273ZJ-135**  
Wall Mounting Bracket



**DS-1273ZJ-135B**  
Wall Mounting Bracket



**DS-1280ZJ-DM21**  
Junction Box



**DS-1271ZJ-135**  
Pendant Mounting Bracket



**DS-1275ZJ**  
Vertical Pole Mounting Bracket



**DS-1281ZJ-DM23**  
Inclined Base Mounting Bracket

Distributed by



# HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Africa**  
T +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761