

Features:

- > Wireless N transfer speed up to 300Mbps
- > High transmission power to boost wireless signal for further distance
- > Provides powerful Wi-Fi coverage that easily penetrates walls obstructions and eliminates dead zones
- > DC power input and alternative passive PoE ability for flexible deployment
- > Stylish ceiling-mounted appearance for easy Installation to wall or ceiling surface
- > Supports Access Point, AP Router, Client, WDS, Repeater, and WISP modes
- > Zero configuration under default Access Point mode
- > Quick setup, with built-in multilingual management page

What it does:

The netis 300Mbps Wireless N High Power Ceiling-Mounted Access Point WF2520P provides long range, high performance wireless Internet access over large areas. It provides you multiple wireless modes including Access Point, AP Router, Client, WDS, Repeater, and WISP, for flexible wireless network setup and deployment. Also, with the passive PoE design, you may easily establish a solution where electrical socket is unavailable or hard to reach. Under the high power mode, you will enjoy much better network experience in large homes, multi-floor offices or warehouses.

www.netis-systems.com

300Mbps Wireless N High Power Ceiling-Mounted Access Point (Passive PoE)

Specification:

andards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 300Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	<20dBm (For countries using CE Standards) <30dBm (For countries using FCC Standards)
Data Transfer Rates	802.11n: 40MHz (300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Mode	Access Point, Client, WDS, AP+WDS, Client+Repeater
Wireless Security	WEP (64/128-bit), WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK Mixed Mode SSID Broadcast Enable/Disable MAC Address Filtering

Hardware	
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interfaces	WAN/PoE: 10/100Mbps Auto MDI/MDIX RJ45 LAN port, Passive PoE Supported LAN: 10/100Mbps Auto MDI/MDIX RJ45 LAN port
LED Indicators	System, Wi-Fi
Button	RESET
Antennas	2* Internal Antenna
Power Supply	Passive PoE/ DC 24V/0.5A (Output)

	Power Supply	Passive PoE/ DC 24V/0.5A (Output)
	Software	
	Operation Modes	AP, AP Router, WISP
	WAN Connection Types	DHCP, Static IP, PPPoE, Russia PPPoE, L2TP/Russia L2TP, PPTP/Russia PPTP
	Port Forwarding	Virtual Servers, UPnP, DMZ
	QoS	Bandwidth Control
	Access Control	MAC Filtering
	Others	Dynamic DNS Firmwara Ungrado Backup & Pactore

3			
QoS	Bandwidth Control		
Access Control	MAC Filtering		
Others	Dynamic DNS, Firmware Upgrade, Backup & Restore		
Others			
Certification	FCC, CE		
	Operating Temperature: 0°C~40°C	Storage Temperature: -40°C~70°C	

Storage Humidity: 5%~90% non-condensing

1* 24V/500mA Power Adapter 1* Mounting Kit

1* Quick Installation Guide

Operating Humidity: 10%~90% non-condensing

1* WF2520P 1* PoE Power Injector 1* Ethernet Cable

Topological Graph:

Environment

Package

