



## PowerWalker VI 1000 LCD/FR

Line-Interactive UPS

1000VA Line-Interactive UPS

2x French & 2x IEC outlets, RJ11/RJ45 Surge Protection

**USB** Connection for monitoring

LCD display for status view

Built-in boost and buck AVR function



Item-No. 10120045















USB Port



IEC Outlets

AVR (Autom. Voltage Regu-lator)

Security Port

Software

**Product Features** 

PowerWalker VI 1000 LCD/FR is a Line- Interactive UPS which provides high performance and reliable and cost-effective backup power protection. The UPS can be automatically started up without AC power supplied. In addition, this UPS provides RJ11/RJ45 surge protection, and green power function for energy saving. Equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or SMB (small medium business) application.

- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Simulated sine wave
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ11/RJ45 surge protection
- Monitoring software included
- LCD display for status view
- Green function for energy saving (can be enabled by Software)









## **Technical Details**

Proc	luct	<b>Features</b>	
FIUL	ıucı	i catules	

Capacity	1000VA / 600W	
Input		
Voltage	220/230/240VAC	
Voltage Range	160-290VAC	
Output		
Voltage	220/230/240VAC	
Voltage Regulation	± 10 % (Battery Mode)	
Frequency	50 or 60Hz	
Freq. Regulation	±1 Hz (Battery Mode)	
Waveform	Modified Sine wave	
Transfer Time		
Typical	2-6ms	
Battery		
Туре	12V / 7Ah	
Quantity	2 x	
Recharge Time	4h to 90%	
<b>Full Protection</b>		
Discharge	Yes	
Overcharge	Yes	
Overload	Yes	
LCD Display		
LCD Indicators	AC mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm and Low battery alarm.	
Audio Indicators		
Battery Mode	Beep every 10sec	
Low Battery	Beep every second	
Fault	Beep every 0.5sec	
Battery Weak	Beep every 2sec	
Battery faulty	Continuously sounding	

## **Connections**

Communication	USB		
Outlets	2x French, 2x IEC		
Surge Protection	RJ11/RJ45 (in/out)		
Software & System Requirements			
Software	ViewPower		
Operating System	For details visit: www.powerwalker.com/viewpower.html		
Other	1x USB port		
<b>Product Details</b>			
Dimensions	350 x 146 x 165 mm		
Colour	Black		
Weight UPS case	8.0kg		
Model Code	VI 1000 LCD/FR		
Environment			
Temperature	0°C – 40°C		
Humidity	0 - 90% (non-condensing)		
Package Content	t		
Package Content	PowerWalker VI 1000 LCD/FR,		
	IEC cable, manual,		
	Software CD, USB cable		
Logistic Data			
Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR		
	RU/UA/BY/PL/CZ/HR/HU/BG/KK/SR		
Manual Language	EN/DE/FR/PL/CZ		
Dimension/Giftbox	455 x 195 x 255 mm		
Weight/Giftbox	9.0kg		
Pieces/Carton	1		
Pieces/Palette	72		
Item Number	10120045		
EAN	4260074975017		
Warranty	24 Month (except battery)		

Version: EN 30/04/2012

We reserve the right for technical changes and mistakes

Use UPS configurator on <a href="www.powerwalker.com">www.powerwalker.com</a> for detailed backup time information.